Landsat 7 Processing System CDR



Landsat 7 Processing System (LPS)

Critical Design Review

November 17, 1995

Landsat 7 Processing System CDR



Agenda

Introduction	
--------------------------------	--

J. Henegar

Design Overview

R. Schweiss

T. Aslam

• LPS Hardware Architecture

C. Brambora

• LPS Operational Scenarios

R. Schweiss

SWCI Detailed Design

J. Hosler

D. Crehan

System Testing

J. Henegar

Acceptance Testing

EDC

Facilities

EDC

Conclusion

J. Henegar

Landsat 7 Processing System CDR



Agenda

•	Intro	duction
---	-------	---------

J. Henegar

Purpose and Scope Documentation SDR/SSR Followup Context Diagram

Design Overview

- R. Schweiss
- T. Aslam
- LPS Hardware Architecture
- C. Brambora
- LPS Operational Scenarios
- R. Schweiss

SWCI Detailed Design

- J. Hosler
- D. Crehan

System Testing

J. Henegar

Acceptance Testing

EDC

Facilities

EDC

Conclusion

J. Henegar

Landsat 7 Processing System CDR



LPS CDR Technical Review Panel

- Ludie Kidd/510 Chair
- Jim Andary/430
- Bill Potter/511
- Jim Irons/923
- Armen Caroglanian/531
- Ted Ackerson/505
- John Boyd/EDC
- Mike Mignogno/NOAA
- Jim Ellickson/NOAA
- Madeline Butler/501
- Tom Bialas/514





Purpose and Scope

- Purpose of CDR
 - Present synopsis of LPS Detailed Design Specification and related design material
- Scope of LPS Detailed Design
 - Detailed design encompasses:
 - » Defining detailed design for software and hardware Cl's
 - » Refining detailed inter-subsystem interfaces, refining external interfaces
 - » Defining a detailed design for the operator-system interface
 - » Defining a detailed design for the database
 - » Refining operations scenarios
 - » Performing further studies and prototypes to guide design
 - » Defining final test plans
 - » Documenting the above in specifications, ICD's, plans, etc





Documentation

- Accompanying Documentation
 - LPS Detailed Design Specification
 - LPS Interface Definition Document
 - LPS-IAS Interface Control Documentation
 - LPS System Integration and Test Plan
 - LPS Build Implementation Plan
 - LPS User's Guide (Preliminary)
 - LPS Output Files Data Format Control Book

 All documentation is available on-line from the Landsat Processing System server. Instructions for access are included in the back of the package





Review Item Dispositions

• Please submit RIDS to: Phil Province (bldg 23, RM C429, 286-7731) no later than December 8, 1995





LPS SDR/SSR Follow-up

- 23 RIDS and 5 Action Items received as result of the LPS SDR/SSR conducted March, 1995
 - All RIDS were responded to and concurred by the originator. Appropriate documentation was updated as necessary.





RID/AI Summary

Major Catagories of RIDS

- Inconsistencies in System Design Spec and Software Requirements Spec.
 - Inconsistencies were corrected in signature version of SDS and SRS
- Failover and use of Integration and Test Recorders
 - Approaches to use of the Integration and Test Recorders were provided
- Metadata Contents updates
 - Appropriate fields were added to the metadata contents and F&PS was updated accordingly
- Data Quality Assurance and Trending Analysis
 - Working with Project Science Office to provide impacts to the Project
- LGS Interface Control Document Comments
 - Items were incorporated into the signature version of the ICD

Landsat 7 Processing System CDR



RID/AI Summary

Action Item Summary

Al 03-09-95-01 Confirm contact period duration

 14 minutes is the maximum contact duration for EDC 0 Degree Acquisition Circle

AI 03-09-95-02 Use of hardware for some LPS functions

 Trade studies were performed and presented as part of the LPS System Design Review showing that a predominantly software approach was advantageous, cost effective, and feasible

Al 03-09-95-03 Identify alternative RAID hardware vendors

Alternatives are available in industry and identified in Action Item response

Landsat 7 Processing System CDR



RID/AI Summary

Action Item Summary

- Al 03-09-95-04 Obtain written statements for vendor support and demonstrate that s/w is portable
 - Written statements are attached to action item response.
 - Software portability is not a requirement, however, LPS has adopted proven approach for minimizing portability problems. LPS will be POSIX compliant were ever possible and isolate and clearly document any non-POSIX implementations. This has been proven effective by Pacor II portability exercises.
 - Working with SGI to obtain continued support for the device drivers for data capture
- AI 03-09-95-05 Use of Spacecraft I&T Recorders
 - Covered under RID Response





High Level Requirements

Functional Requirements

- Receive and record raw Landsat 7 wideband data from the LGS for 4 wideband data inputs simultaneously on a contact basis
- Perform CCSDS Grade 3 Service on all received wideband data
- Perform BCH Error Detection and Correction on all wideband data
- Generate Level 0R data files on a subinterval basis
- Generate Browse Data files on a scene basis
- Generate Metadata data files on a subinterval basis
- Provide return link quality and accounting as part of metadata
- Perform Automated Cloud Cover Assessment
- Identify WRS scene boundaries
- Coordinate the transfer of all Level 0R related data files to the Land Processes (LP DAAC)





High Level Requirements (cont)


Performance Requirements

- Receive and record the raw wideband data at 75Mbps for each input data stream
- Process the equivalent of 250 ETM+ scenes per day
- Process and notify the LP DAAC of data availability within 16 hours of receipt of data
- Provide the capability to reprocess up to 10 percent of the wideband data on a daily basis
- Retain raw wideband data for a minimum of 30 days from time of receipt
- Process received wideband data at an average aggregate rate of 12 Mbps (goal is to process at an average aggregate rate of 30 Mbps, which is 7.5Mbps per input string)
- Sustain operations 24 hours a day, 7 days a week for a minimum mission life of 5 years

Landsat 7 Processing System CDR



LPS Context Diagram







LPS Context Diagram

- LGS

- » Coordinate with LGS to capture raw wideband data on contact basis
- » Receive raw wideband data at 75 Mbps on four physical channels

- MOC

- » Provide data receive summary report
- » Provide non-nominal return link quality statistics

- IAS

- » Receive Parameters for sensor alignment and scene identification
- » Receive anomalous image quality statistics

- LP DAAC

- » Notify LP DAAC of data availability
- » Receive Data Delivery Notice from the LP DAAC

Landsat 7 Processing System CDR



Operations Concept

